



UNIPACK PCR  
STANDARD  
UPDATE ON 2017-05-10

---

## 1. Description of product

<b>Product</b>	:	UNIPACK PCR self-adhesive document pouch
<b>Sizes</b>	:	Standard: C7, C6, C5, C4, LD special formats available
<b>Use</b>	:	for transport of freight accompanying documents, instruction sheets or other documents
<b>Manufacturer</b>	:	<b>Anton Debatin GmbH</b> <b>Vichystraße 6</b> <b>D- 76446 Bruchsal</b> <b>+49 (0) 7251 – 8009 – 100</b> <a href="http://www.debatin.de/">http://www.debatin.de/</a>

---

## 2. Material

Film	:	PE, manufactured from > 60 % recycled material <b>PCR</b> -> <b>Post Consumer Recycling</b>
Adhesive	:	high adhesive power, solvent-free
Backing paper	:	one-side siliconised, FSC®- certified
Colours	:	solvent based colours During the production process the solvent apours are extracted and recycled thermally.

---

## 3. Closure systems

Closure	:	adhesive closure (bag opening)
---------	---	--------------------------------

---

## 4. Print

Scripture	:	„PACKING LIST“, „PACKING LIST – INVOICE“, „DOCUMENTS“, „DOCUMENTS ENCLOSED“, „DOCUMENTS CI-INCLUS“. multilingual scripture
Special printing:	:	up to 4 colours

---



UNIPACK PCR  
STANDARD  
UPDATE ON 2017-05-10

---

## 5. Sealing

Type of sealing : flat sealing

---

## 6. Packaging

C6	:	1 000 pcs. / carton	96 000 pcs. / pallet
LD	:	1 000 pcs. / carton	96 000 pcs. / pallet
C5	:	1 000 pcs. / carton	72 000 pcs. / pallet

Packaging of 250 pcs. possible.

---

## 7. Processing

After removing the protection paper press firmly over the entire bag surface. The bags should be fixed at temperatures of  $> +10^{\circ} \text{C}$ .

---

## 8. Durability and Stocking

When kept in a dark and dry place at room temperature (between  $+10^{\circ} \text{C}$  and  $+30^{\circ} \text{C}$ ), the pouches can last for 2 years.

---

## 9. Disposal

The product is recyclable, disposable in landfills (domestic waste), can be burnt in modern municipal waste incinerators.

---

The information presented in this leaflet is based on our present level of technical knowledge and experience and reflects averages. Due to the abundance of possible influences during the use and application of our products this information does not relieve the user of conducting his own tests and experiments. No legally binding guarantee of certain features or of suitability for any particular purpose can be deducted from it. Possible patent rights and existing laws and regulations must be observed by the user as his own responsibility. Technical modifications reserved.