





DEBACOR CORTEC® VpCI® Hand Wrap Stretch

Film is the ultimate high performance film, developed for corrosion protection of ferrous and non-ferrous metals. This film is coextruded using state-of-the-art resins, which offers superior strength and stretch characteristics as well as multimetal corrosion inhibiting properties that only VpCI technology can deliver. DEBA**COR CORTEC® VpCI® Hand Wrap Stretch Film** delivers puncture resistance and load holding, which allows a user to down-gauge, contain aggressive loads, and produce a better package at reduced cost.









Disclaimer

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed. Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer. Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DEFERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE. AND IS ALL RISK AND LIABILITY WHATS/COVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation. THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. FOR INDUSTRIAL USE ONLY. KEEP OUT OF REACH OF CHILDREN. KEEP CONTAINER TIGHTLY CLOSED. NOT FOR INTERNAL CONSUMPTION.







The combination of enhanced polyethylene resins with VpCI technology makes DEBA**COR CORTEC*** **VpCI*** **Hand Wrap Stretch Film** the most advanced corrosion inhibiting stretch film available today on the market.



Method of Application

DEBA**COR** *CORTEC** *VpCI** *Hand Wrap Stretch Film* is compatible with commercially available manual and automatic stretch wrapping equipment.

Benefits

- Does not contain polyisobutylene (PIB) or other tackifiers in cling layer, allowing discarded stretch film to be recycled
- Does not leave residue on parts
- Provides multimetal corrosion protection with VpCI action
- Protected parts can be used immediately without cleaning or degreasing
- More economical and secure than tape, twine, or strapping
- Holds protected parts securely in place
- Self-adhering film bonds to each layer for added strength

- Helps keep dust, dirt, and moisture off warehouse stock
- Superior performance in light gauges allows downgauging and cost effectiveness
- Can be applied with standard equipment
- Excellent clarity and cling
- Up to a 3:1 stretch ratio
- FDA approved for use on food handling equipment
- Recyclable, environmentally friendly

Packaging and Storage

Available in standard machine film sizes and gauges. DEBACOR CORTEC® VpCI® Hand Wrap Stretch Film should be stored indoors at room temperature, sealed in its original packaging.

Typical mechanical properties of DEBACOR CORTEC® VpCI® Hand Wrap Stretch Film

Property		Test Method	Units		
Caliper		ASTM D6988	Microns 25		50
Breaking Factor	MD	ASTM D882-02	N	28,61	50,13
	TD	ASTM 0882-02		27,22	47,77
Tensile Strength at Break	MD	ASTM D882-02	N/mm²	33,34	36,16
	TD	A5114 D002-02		34,41	37,02
Elongation at Break	MD	ASTM D882-02	%	647.17	680.05
	TD	ASTM D882-02		730.74	737.11
Tear Strenght	MD	ACTM D1022 OC -	mN	1569.60	5179.68
	TD	ASTM D1922-06a		5791.83	11379.60
Dart Drop Impact Resistance		ASTM D1709-04, Test Method A	grams	819.16	> 1300
Coefficient of Friction	Static	ASTM D1894		1.20	0.40
	Kinetic			1.23	0.47

^{*}Typical properties represent average laboratory values and are not intended as specifications but as guides only.

CORTEC* VpCI* Stretch Film is produced by Cortec Corporation and EcoCortec (a European Subsidiary of Cortec Corporation)

DEBACOR CORTEC® VpCI® Hand Wrap Stretch Film

Article no.	roll width in mm	strength in µm	meter/roll	kg/roll	core diameter	No. on pallet
112H0000179	500	35	165	2,9	50	120